


RACE		BASIC SET-UP	
TRACK			
NAME			
CITY / COUNTRY			
CONTACT			
DATE	TEMPERATURE / °F OR °C	AIR	TRACK
QUALIFYING POSITION	BEST LAPTIME / SEC	FINAL POSITION	RACE LENGTH / MINUTES
TRACK CONDITION	<input type="checkbox"/> SMOOTH <input type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST	
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH		
FRONT	DIFF	REAR	
80 K	GEAR DIFF. OIL /cst	60 K	
ONE WAY DIFFERENTIAL <input type="checkbox"/> YES			
SOLID ONE WAY DIFE <input type="checkbox"/> YES			
SOLID AXLE <input type="checkbox"/> YES	SOLID AXLE <input type="checkbox"/> YES		
GEARING			
PINION	1ST 15 <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 17 <input type="checkbox"/> 18 <input type="checkbox"/>	SPUR	1ST 57 <input type="checkbox"/> 58 <input type="checkbox"/> 59 <input checked="" type="checkbox"/> 60 <input type="checkbox"/>
	2ND 20 <input type="checkbox"/> 21 <input checked="" type="checkbox"/> 22 <input type="checkbox"/> 23 <input type="checkbox"/>		2ND 53 <input type="checkbox"/> 54 <input checked="" type="checkbox"/> 55 <input type="checkbox"/>
PULLEY	25 <input checked="" type="checkbox"/> 26 <input type="checkbox"/>	RATIO 1ST	RATIO 2ND
FRONT	SHOCKS	REAR	
STANDARD	SPRING	STANDARD	
600	OIL /cst	600	
0	REBOUND %	0	
<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES	PISTONS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES	
	1.0mm <input type="checkbox"/> 1.1mm <input checked="" type="checkbox"/> 1.2mm <input type="checkbox"/>		
	OTHERS		
FRONT	ANTI-ROLL BAR	REAR	
<input type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°	<input type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°	<input type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°	
STANDARD <input type="checkbox"/> <input type="checkbox"/> 0.7 mm	BLADE	OPTION <input type="checkbox"/>	
2.6	WIRE /mm	2.0	
0		0	
FRONT	TIRES	REAR	
LEFT	RIGHT	LEFT	RIGHT
	MANUFACTURER		
	SHORE /deg°		
	DIAMETER /mm		
	5 MIN. WEAR /mm		
	RUBBER TIRES		
ENGINE			
ENGINE			
CARB. DIA /mm	HEAD SHIM /mm	PLUG	
MUFFLER	FUEL		
CLUTCH / BRAKE			
FLYWHEEL	<input checked="" type="checkbox"/> STANDARD		
CLUTCH FLYWEIGHTS	<input checked="" type="checkbox"/> STANDARD		
CLUTCH SHOE	Yellow	CLUTCH SPRING	<input checked="" type="checkbox"/> STANDARD
CLEARANCE /mm	ADJ. NUT /mm		
BRAKE PAD	<input checked="" type="checkbox"/> STANDARD		
BODY			
WING HEIGHT	WING POSITION	WING ANGLE	
COMMENTS			

